

LOXIM 800 00 HB

Polypropylene

LOXIM Industries Private Limited

Message:

LOXIM 800 00 HB is a Polypropylene product. It is available in Asia Pacific. Primary characteristic: flame rated.

General Information			
Appearance		Colors Available	
		Opaque	
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.848 to 0.948	g/cm ³	ASTM D792
Molding Shrinkage - Flow	1.7 to 2.3	%	ASTM D1299
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	34.0 to 36.0	MPa	ASTM D638
Flexural Modulus	1300 to 1500	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	30 to 40	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	90.0 to 100	°C	ASTM D648B
Flammability	Nominal Value		Test Method
Flame Rating (1.60 mm)	HB		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT