

PETILEN H2-8

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

Message:

PETILEN H2-8 is a Low Density Polyethylene product. It can be processed by blow molding or injection molding and is available in Asia Pacific, Europe, or North America. Applications of PETILEN H2-8 include bottles, caps/lids/closures, consumer goods and kitchenware.

General Information			
Uses	Bottles		
	Caps		
	Cups		
	Toys		
Forms	Pellets		
Processing Method	Blow Molding		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.918 to 0.922	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.7 to 3.0	g/10 min	ASTM D1238
Optical	Nominal Value		Test Method
Gloss	70		ASTM D2457
Additional Information	Nominal Value		
Film Quality ¹	A		
NOTE			
1.	ALKATHENE 36		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT