

# SABIC® PP 49MK45

Polypropylene Impact Copolymer

SABIC Americas, Inc.

## Message:

### Product Description

PP 49MK45 is specially developed for producing injection molded articles. This grade contains nucleating- & antistatic agents. It has medium flow properties , good impact resistance (even at low temperature) and good stiffness.

### Typical Applications

PP 49MK45 can be used for houseware, garden furniture , toys, containers & pails.

General Information			
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	High Stiffness		
	Impact Copolymer		
	Low Temperature Impact Resistance		
	Medium Flow		
	Medium Impact Resistance		
	Nucleated		
Uses	Containers		
	Household Goods		
	Outdoor Applications		
	Outdoor Furnishings		
	Pails		
	Toys		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.905	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	21	g/10 min	ASTM D1238
Molding Shrinkage	1.2 to 2.5	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale, Injection Molded)	98		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 1% Secant (Injection Molded)	1500	MPa	ASTM D638
Tensile Strength (Yield, Injection Molded)	27.0	MPa	ASTM D638

Tensile Elongation (Yield, Injection Molded)	7.0	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-20°C, Injection Molded	50	J/m	
23°C, Injection Molded	85	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	105	°C	ASTM D648
Vicat Softening Temperature	151	°C	ASTM D1525 <sup>1</sup>
Injection	Nominal Value	Unit	
Rear Temperature	200 to 250	°C	
Middle Temperature	200 to 250	°C	
Front Temperature	200 to 250	°C	
Mold Temperature	15.0 to 40.0	°C	
NOTE			
1.	Rate B (120°C/h)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT