

# TOTAL Polypropylene PPH 3925WZ

Polypropylene Homopolymer

TOTAL Refining & Chemicals

Message:

Total Petrochemicals Polypropylene 3925WZ is nucleated to provide fast cycle time and improve contact clarity. 3925WZ contains an antistat that will help protect molded parts from shelf dusting. 3925WZ complies with all applicable FDA regulations for food contact applications. 3925WZ is recommended for thin wall parts, caps and closures in multi-cavity molds.

General Information			
UL YellowCard	E66261-247994		
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	Contact Clarity		
	Fast Molding Cycle		
	Food Contact Acceptable		
	Good Flow		
	Good Stiffness		
	Nucleated		
Uses	Caps		
	Closures		
	Thin-walled Parts		
Agency Ratings	EC 1907/2006 (REACH)		
	FDA Food Contact, Unspecified Rating		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.905	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	60	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	107		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1790	MPa	ASTM D638
Tensile Strength (Yield)	37.9	MPa	ASTM D638

Tensile Elongation (Yield)	10	%	ASTM D638
Flexural Modulus	1830	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	21	J/m	ASTM D256A
Unnotched Izod Impact (23°C)	850	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	127	°C	ASTM D648
Melting Temperature	166	°C	DSC
Injection	Nominal Value	Unit	
Processing (Melt) Temp	200 to 232	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

