

# Globalprene® 5517

Styrene Isoprene Styrene Block Copolymer

Lee Chang Yung Chemical Industry Corp.

Message:

Globalprene® 5517 is a Styrene Isoprene Styrene Block Copolymer (SIS) material. It is available in Asia Pacific or North America.

Important attributes of Globalprene® 5517 are:

REACH Compliant

RoHS Compliant

Copolymer

Linear Polymer Structure

Low Viscosity

Typical application of Globalprene® 5517: Adhesives/Tapes

General Information			
Features	Block Copolymer		
	Linear Polymer Structure		
	Low Viscosity		
Uses	Adhesives		
Agency Ratings	EC 1907/2006 (REACH)		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.930	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	20	g/10 min	ASTM D1238
Ash Content	0.70	%	ASTM D5667
Styrene Content	15	%	ASTM D5775
Viscosity - 25wt% Toluene Viscosity	900	mPa · s	ASTM D2196
Volatile Matter	0.25	%	ASTM D5668
Diblock Content	38	%	ASTM D5296

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT