

# ExxonMobil™ LDPE LD 201.48

Low Density Polyethylene Resin  
ExxonMobil Chemical

Message:

LD 201.48 is a low density polyethylene extrusion coating grade with excellent processability and combination of heat sealability and adhesion. It has: excellent shrinkage/drafting balance, so low-level edge trimming is required, which means that waste can be reduced and processing speed can be increased. -Good water vapor isolation, such as for single-piece packaging purposes (sugar, salt)

General Information			
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	4.2	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	95.0	°C	ASTM D1525
Legal statement			

有关潜在食品接触应用合规信息(例如:FDA,EU,HPFB),请与埃克森美孚化工客户服务代表联系.本产品不宜在医疗应用中使用,亦不应在任何此类应用中使用

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

