

# Jampilen HP561S

Polypropylene Homopolymer

Jam Polypropylene Company

## Message:

Jampilen HP561S is a very narrow molecular weight distribution homopolymer, suitable for extrusion applications. It is formulated with an anti-gasfading stabilisation package. Jampilen HP561S is designed for production of continuous filaments. Typical applications are HTY and spunbond nonwoven.

General Information			
Features	Controlled Rheology		
	Gas-fading Resistant		
	Homopolymer		
	Narrow Molecular Weight Distribution		
Uses	Agricultural Applications		
	BCF Yarn		
	Disposable Fabrics		
	Filaments		
	Geo Membranes		
	Nonwovens		
	Spunbond Nonwovens		
	Yarn		
Processing Method		Filament Extrusion	
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	33	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1450	MPa	ISO 527-2
Tensile Stress (Yield)	33.0	MPa	ISO 527-2
Tensile Strain			ISO 527-2
Yield	10	%	
Break	> 50	%	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	97.0	°C	ISO 75-2/B
Vicat Softening Temperature	152	°C	ISO 306/A50

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

