Axiall PVC 8553

Flexible Polyvinyl Chloride Axiall Corporation

Message:

A general purpose profile extrusion compound with excellent weathering properties.

One collection of the			
General Information			
Features	General Purpose		
	Good Weather Resistance		
Uses	General Purpose		
	Profiles		
Processing Method	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	55		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
	7.24	MPa	
100% Strain	2.76	МРа	
Tensile Elongation (Break)	360	%	ASTM D638
Extrusion	Nominal Value	Unit	
Melt Temperature	166	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

