

Jam PE 10501

Very Low Density Polyethylene

Jam Petrochemical Company

Message:

Jam PE 10501 is a Very Low Density Polyethylene product. It is available in Africa & Middle East. Applications of Jam PE 10501 include coating applications, fabrics/fibers and film.

General Information			
Uses	Film		
	Laminates		
	Monofilaments		
Physical	Nominal Value	Unit	Test Method
Density	0.910 to 0.912	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.95	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	25	µm	
Dart Drop Impact (25 µm, Blown Film)	210	g	ASTM D1709A
Elmendorf Tear Strength			ASTM D1922
MD : 25 µm, Blown Film	200	g	
TD : 25 µm, Blown Film	400	g	
Optical	Nominal Value	Unit	Test Method
Gloss (45°, 25.0 µm, Blown Film)	35		ASTM D1790
Haze (25.0 µm, Blown Film)	25	%	ASTM D1003
Additional Information	Nominal Value	Unit	
Fish Eye	80.0	No./m ²	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT