

Varcum 29217R

Phenolic

Durez Corporation

Message:

Varcum 29217R is a highly condensed, one-step, pulverized phenolic resin.
Formulating of brake blocks and brake linings.
Recommended for use in dry mix frictional formulations.
Displays stable frictional characteristics under heavy duty braking conditions.

General Information			
Uses		Automotive Applications	
		Liners	
Physical	Nominal Value	Unit	Test Method
Moisture Content - Karl Fischer	< 1.5	%	Internal Method
Softening Point ¹	65	°C	Internal Method
Inclined Plate Flow (125°C)	4.00	cm	Internal Method
Screen Mesh ²	< 1.0	%	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Post Cure Time (160°C)	0.011	hr	
NOTE			
1.	cap. shrink		
2.	200 Mesh		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT