

Lusin® Alro OL 151

Unspecified

Chem-Trend L.P.

Message:

Special Silicone-free Release Agent for Processing Thermoplastic Resins

Benefits

For application temperatures up to 150°C (302°F)

Long cycle time

Wide range of applications

Description

Lusin® Alro OL 151 is a silicone-free release agent on the basis of synthetic oils and additives. It is suitable for an application temperature (mould temperature) of up to 150°C (302°F). Besides excellent release properties, Lusin® Alro OL 151 also shows excellent slip effects combined with high pressure resistance.

Typical Properties

Appearance of the active ingredient: Liquid, green

Application

A fine even spray film should be applied to the clean mould especially to edges and undercuts. For cleaning we recommend the use of Lusin® L 21 F as mould cleaning agent and Lusin® Clean L 11 or Lusin® Clean L 51 as degreasing agent.

Should subsequent treatment of the parts be required, e.g. metal coating, lacquering, etc. we recommend that preliminary tests should be carried out.

Residues of the release agent are easily removed by rinsing the parts in a mixture of water and cleaner (e.g. Lusin® Clean W 81).

General Information

| | |
|------------|--------|
| Appearance | Green |
| Forms | Liquid |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

