

Vatpol 300

Polyethylene

Vatan Plastik San. Tic. AS

Message:

Vatpol 300 is a Polyethylene material filled with 60% calcium carbonate. It is available in Africa & Middle East, Asia Pacific, or Europe for blow molding, film extrusion, injection molding, or thermoforming.

Typical applications include:

Additive/Masterbatch

Bags/Liners

Bottles

Film

General Information	
Filler / Reinforcement	Calcium Carbonate,60% Filler by Weight
Additive	Titanium Dioxide (TiO2)
Uses	Bags
	Blending
	Bottles
	Film
	Plastics Modification
Appearance	White
Forms	Granules
Processing Method	Blow Molding
	Film Extrusion
	Injection Molding
	Thermoforming

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.46 to 1.50	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.30 to 0.50	g/10 min	ASTM D1238
Ash Content (600°C)	59 to 61	%	ISO 3451-1
Moisture	< 3.0	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

