

Hangzhou Jinxin Colored VMPET Film

PET Film

Hangzhou Jinxin Filming Packaging Co., Ltd.

Message:

Product performance:
Aluminum layer have strong adhesion, high brightness
Bright color uniformity,Color with good fastness
have excellent Ink adsorption properties
Application: Commonly used in the cigarette box, wine box composite and some gift packaging. Also can be used in outdoor protection rescue.

General Information			
Features	Good Adhesion		
	Metallized		
Uses	Packaging		
	Tobacco Overwrap Flexible Packaging		
Forms	Film		
Mechanical	Nominal Value	Unit	Test Method
Coefficient of Friction	0.48		ASTM D1894
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	12	μm	ASTM D374
Tensile Strength			ASTM D882
MD : Break	235	MPa	
TD : Break	241	MPa	
Tensile Elongation			ASTM D882
MD : Break	130	%	
TD : Break	110	%	
Optical	Nominal Value		Test Method
Gloss	139		ASTM D2457
Additional Information	Nominal Value	Unit	Test Method
Heat Shrinkage ¹			ASTM D1204
MD	1.6	%	
TD	0.0	%	
Wetting Tension - Non plated surface	44	dyne/cm	ASTM D2578
NOTE			
1.	150°C/30min or 190°C/5min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

