

Durez® 33458

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 33458 is a white pulverized thermosetting two-step phenolic resin.

Durez 33458 is recommended for use in the manufacture of dry mix brake linings, particularly those of the semi-metallic type.

General Information			
Uses	Automotive Applications Liners		
Appearance	White		
Thermoset	Nominal Value	Unit	Test Method
Post Cure Time (165°C)	9.6E-3	hr	
Additional Information	Nominal Value	Unit	Test Method
Hexa	8.1	%	Internal Method
Inclined Plate Flow (125°C)	3.50	cm	Internal Method
Screen Mesh ¹	< 3.0	%	Internal Method
NOTE			
1.	200 Mesh		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT