

# KEP® 350

Ethylene Propylene Diene Terpolymer

Kumho Polychem Co., Ltd.

## Message:

### Features:

High mooney viscosity & excellent processability, ultra-high vulcanization speed, blend with diene rubber

### Applications:

Tire coverstrip, white sidewall, window seals, gaskets, packings, sponges

General Information		
Features	Good Processability	
	High Viscosity	
	Vulcanizable	
Uses	Automotive Applications	
	Blending	
	Industrial Applications	
	Seals	
	Windows & Doors	
Forms	Bale	
Physical	Nominal Value	Unit
Mooney Viscosity (ML 1+4, 125°C)	56	MU
Ethylene Content	57.0	wt%
Ethylidene Norbornene (ENB) Content	7.9	wt%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

