

INEOS PP 200-GA02

Polypropylene Random Copolymer

INEOS Olefins & Polymers Europe

Message:

200-GA02 is a general purpose random copolymer intended for extrusion applications requiring low melt flow and good melt strength.

Applications

Sheet extrusion for stationery applications

Thermoforming

Benefits and Features

Improved processability

Low stress whitening under bending

Excellent colour and temperature stability

General Information	
Features	General Purpose
	Good Color Stability
	Good Melt Strength
	Good Processability
	Good Thermal Stability
	Low Flow
	Random Copolymer
Uses	General Purpose
	Sheet
	Stationary Supplies
RoHS Compliance	Contact Manufacturer
Forms	Pellets
Processing Method	Sheet Extrusion
	Thermoforming

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	2.0	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	27.0	MPa	ISO 527-2
Flexural Modulus (23°C)	950	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	10	kJ/m²	ISO 180/1A
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	149	°C	ASTM D3417

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

