Deco-Coat™ UV Cure 7156™

Epoxy; Epoxide

Epoxies, Etc.

Message:

UV Cure 7155[™] and 7156[™] are low intensity UV Curable Epoxy Resins. These products are water clear and cure to a smooth, bubble free finish. Low cost, low intensity lights are all that is needed to cure these unique polymer systems. UV Cure 7155[™] and 7156[™] also have superior aging and yellowing resistance.

Applications:

UV Cure 7155^{TM} and 7156^{TM} may be used as decorative ultra clear doming resins on labels, pins, key fobs, magnets, ceramics, etc... UV Cure 7155^{TM} and 7156^{TM} have outstanding adhesion to photographic paper. Their high gloss finish and outstanding clarity will enhance any image it is applied over. These materials can also be used as protective coatings due to their ability to resist moisture, chemicals and thermal shock.

Benefits:

No weighing or mixing

General Information

Single component

Cures in minutes

Non-solvent 100% solids system

Can be cured with low intensity black light

Features	Good Adhesion							
	Good Chemical Resistance Good Flexibility Good Thermal Shock Resistance							
					High Clarity			
					High Gloss Moisture Resistant UV Curable			
	Uses	Coating Applications						
		Decorative Parts						
		Labels						
Appearance	Clear/Transparent							
Uncured Properties	Nominal Value	Unit						
Color	Clear/Transparent							
Solids Content	100	%						
Density (25°C)	1.09	g/cm³						
Viscosity (25°C)	1.0	Pa·s						
Shelf Life (4°C)	6	month						
Cured Properties	Nominal Value	Unit						
Shore Hardness (Shore A)	95							
Tensile Strength	60.7	MPa						
Tensile Elongation at Break	6.1	%						
Relative Permittivity (60 Hz)	3.16							

Volume Resistivity	1.6E+9	ohms·cm	
Dissipation Factor (60 Hz)	0.018		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

