

Escor™ 5200

Ethylene Acrylic Acid Copolymer Resin

ExxonMobil Chemical

Message:

Escor 5200 is an ethylene acrylic acid copolymer with high copolymer monomer composition. Escor 5200 can be used alone or as an ingredient in a mixed formula for bonding purposes, and is suitable for applications requiring medium viscosity and good adhesion to polar materials (metal, nylon, glass, etc.).

General Information			
Physical	Nominal Value	Unit	Test Method
Acrylic Acid Content	15.0	wt%	ExxonMobil Method
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	59.0	°C	ASTM D1525
Legal statement			

有关潜在食品接触应用合规信息(例如:FDA,EU,HPFB),请与埃克森美孚化工客户服务代表联系.本产品不宜在医疗应用中使用,亦不应在任何此类应用中使用

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

