

Catalyst CT/2-OR UV

Polyolefin
Solvay Specialty Polymers

Message:

Catalyst CT/2-OR UV is a polyolefin based masterbatch to be used with Cogegum® GFR/380, and confers improved UV/VIS and aging resistance. It contains also a metal deactivator that allows its use also in direct contact with untinned copper

General Information			
Features	Copper contact stability		
	Halogen-free		
Uses	Wire and cable applications		
RoHS Compliance	RoHS compliance		
Appearance	Natural color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity ¹	1.14	g/cm³	ASTM D792
Apparent Density ²	0.55	g/cm³	ISO 60
Additional Information			
Storage			
The product must be stored under the following conditions:			
closed and undamaged bags			
ambient temperature not exceeding 35°C			
avoid direct exposure to sunlight and weathering			
Product alterations could occur due to extended period of storage			
Shelf life: 12 months			
Solvay Specialty Polymers accepts no liability of any kind in case the above mentioned conditions are not fulfilled.			
Packaging			
25 kg moisture-resistant bags			
NOTE			
1.	Test on the press plate		
2.	Particle test		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT