

Sinvicomp DBS3613

Rigid Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp DBS3613 is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of Sinvicomp DBS3613: Impact Resistant.

Typical applications include:

Electrical/Electronic Applications

Plumbing/Piping/Potable Water

General Information			
Features	Good Impact Resistance		
Uses	Conduit		
	Piping		
Forms	Powder		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.48	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	46.1	MPa	ASTM D638
Tensile Elongation (Break)	150	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	39	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	96.0	°C	ASTM D1525
Heat Stability ¹ (190°C)	30.0	min	BS 2782
NOTE			

1. Congo red@ 190 deg C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT