

# Paracril® C

Acrylonitrile Butadiene Rubber

INSA

## Message:

### Description:

Excellent oil resistance with moderate low temperature flexibility.

High green strength.

Hot polymerized.

Non staining stabilizer.

### Applications:

Automotive products, seals, hoses, o-rings and packings.

Adhesives.

Printing blankets.

General Information	
Features	Good Green Strength
	Low Temperature Flexibility
	Oil Resistant
	Stain Resistant
Uses	Adhesives
	Automotive Applications
	Hose
	Seals

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.990	g/cm <sup>3</sup>	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	73 to 87	MU	ASTM D1646
ACN Content - Bound	33.7 to 36.7	wt%	Internal Method
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT