

Lusin® Protect G 31

Unspecified
Chem-Trend L.P.

Message:

Wax-based Anticorrosion and Lubricating Agent

Benefits

- Stable transparent film; resistant to handling
- Lasting protection against corrosion
- Suitable for the use as a release agent

Description

Lusin® Protect G 31 is a highly efficient anticorrosion agent that also shows lubricating properties. The delayed generation of the solid protective film enables Lusin® Protect G 31 to penetrate into very fine cracks. The protective film is resistant to handling and starts melting at around 50°C (122°F). Lusin® Protect G 31 aerosol contains UV light sensitive pigments enabling the protective film to be visible under UV light (maximum at 366 nm).

Typical Properties

- Corrosion protection per DIN 50017 : No corrosion after 20 h
- Salt spray test per DIN 50021 with 5% NaCl-solution : No corrosion after 28 h

Application

Lusin® Protect G 31 is mainly used to protect moulds and dies dedicated for processing thermoplastic resins against corrosion.

General Information	
Appearance	Clear/transparent
Forms	Liquid

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT