

Shanghai Potomer T-500

Chlorinated Polyvinyl Chloride

Shanghai Potomer International Trade Co., Ltd.

Message:

Features: With excellent solubility, good electric insulativity, thermoplasticity film-forming capacity and extreme chemical stability, it is widely used in producing anti-corrosive plastic products, adhesive and coating, etc.

Uses: coating grade

General Information		
Features	Electrically Insulating	
	Good Corrosion Resistance	
Uses	Coating Applications	
Appearance	White	
Forms	Powder	
Physical	Nominal Value	Unit
Viscosity	1 to 2	mPa·s
Volatile Matter	< 0.30	%
Thermal Stability	> 40	sec
Chloride	61 to 62	%
Granularity - 40 mesh	> 98	%
Oil Absorption	> 30	%
Thermal Decomposition Temperature	> 110	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT