

MTEGRITY™ PP Homopolymer PP710

Polypropylene Homopolymer

M. Holland Company

Message:

MTEGRITY™ PP Homopolymer PP710 is a Polypropylene Homopolymer (PP Homopolymer) product. It can be processed by injection molding and is available in North America. Applications of MTEGRITY™ PP Homopolymer PP710 include caps/lids/closures and consumer goods.

Characteristics include:

- Antistatic
- Homopolymer
- Nucleated

General Information			
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	Homopolymer		
	Narrow Molecular Weight Distribution		
	Nucleated		
Uses	Caps		
	Closures		
	Consumer Applications		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.905	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	35	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	109		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	39.3	MPa	ASTM D638
Tensile Elongation (Yield)	8.5	%	ASTM D638
Flexural Modulus	1760	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	32	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

