## Zhongfa PP FR-08

## Polypropylene

Yuyao Zhongfa Engineering Plastics Co. Ltd.

## Message:

Zhongfa PP FR-08 is a polypropylene material. This product is available in the Asia-Pacific region and is processed by injection molding. The main features of Zhongfa PP FR-08 are: flame retardant/rated flame Flame Retardant Typical application areas include: Electrical/electronic applications electrical appliances

General Information					
UL YellowCard	E228261-229892				
Additive	Flame retardancy				
Features	Flame retardancy				
Uses	Electrical/Electronic Applications				
	Electrical appliances				
UL File Number	E228261				
Forms	Particle				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	0.950	g/cm³	ASTM D792		
Melt Mass-Flow Rate (MFR)	4.8	g/10 min	ASTM D1238		
Molding Shrinkage - Flow	1.7	%	ASTM D955		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	31.0	MPa	ASTM D638		
Tensile Elongation (Break)	26	%	ASTM D638		
Flexural Modulus	1100	MPa	ASTM D790		
Flexural Strength	35.0	MPa	ASTM D790		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (0.45					
MPa, Unannealed)	130	°C	ASTM D648		
Vicat Softening Temperature	135	°C	ASTM D1525		
Flammability	Nominal Value		Test Method		
Flame Rating	V-2		UL 94		
Additional Information					
Notched Izod Impact, ASTM D256: 6 kJ/m <sup>2</sup> Unnotched Izod Impact, ASTM D256: 74 kJ/m <sup>2</sup>					
Injection	Nominal Value	Unit			
Drying Temperature	85.0 - 90.0	°C			
Drying Time	2.0 - 3.0	hr			

Processing (Melt) Temp	185 - 215	°C	
Mold Temperature	40.0 - 80.0	°C	
Injection Pressure	60.0 - 90.0	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

