

Shandong PA612 Type II

Polyamide 612

Shandong Guangyin New Materials Co., Ltd.

Message:

Features and Applications: As one kind of nylon with better tenacity, PA612 is mainly applicable to coating of high-grade toothbrush monofilaments, monofilaments and cables.

General Information			
Uses	Cable Jacketing		
	Filaments		
Physical	Nominal Value	Unit	Test Method
Density	1.04 to 1.08	g/cm ³	ISO 1183
Viscosity	160.000 to 200.000	g/cm ³	
Granularity	30.0 to 50.0	N/g	
Loss on Drying	< 1.0	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	> 50.0	MPa	ISO 527-2
Tensile Strain (Break)	> 150	%	ISO 527-2
Flexural Stress	> 30.0	MPa	ISO 178
Thermal	Nominal Value	Unit	Test Method
Melting Temperature (DSC)	205 to 215	°C	ISO 3146

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT