

Europrene Lattice® 2430

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Europrene Lattice 2430 is an aqueous anionic dispersion of a styrene-butadiene copolymer with high solid content obtained by emulsion polymerisation using fatty acid soap as emulsifier. It does not contain any antioxidant.

Key Features

Europrene Lattice 5577, vulcanised, shows good mechanical properties. It can be used blended with natural latex

Main Applications

Europrene Lattice 2430 is used for high stiffness moulded foams. It can be used for gel and no-gel carpet foams.

| General Information | | | |
|--|----------------|--------|-------------|
| Features | Copolymer | | |
| | Foamable | | |
| | High Stiffness | | |
| Uses | Blending | | |
| | Foam | | |
| Appearance | White | | |
| Forms | Liquid | | |
| Physical | Nominal Value | Unit | Test Method |
| Bound Styrene | 35.0 | % | ASTM D5775 |
| pH | 10.5 | | ASTM D1417 |
| Solids Content | 68.0 | wt% | ASTM D1417 |
| Brookfield Viscosity ¹ (25°C) | 1.10 | Pa · s | ASTM D1417 |
| NOTE | | | |
| 1. | 20 rpm | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT