

Sinpolene MBB2032

Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBB 2032 is a LDPE based black masterbatch designed specifically for use in tubular film blowing, blow moulding and extrusion of polyolefins. SINPOLENE MBB 2032 has high pigment loading and thus offers high coloring value with superior quality and performance. SINPOLENE MBB 2032 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

General Information	
Additive	Carbon black (43%)
Features	General
Uses	Films
RoHS Compliance	RoHS compliance
Appearance	Black
Forms	Particle
Processing Method	Film extrusion Blow molding Extrusion Injection molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.16	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	3.0 - 15	g/10 min	ASTM D1238
Moisture Content		%	ASTM D3030
Carbon Black Content	43	%	ASTM D1603

Additional Information

推荐用量: 2.5-5.0%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT