

SureSpec HD60-800F

High Density Polyethylene

Genesis Polymers

Message:

SureSpec HD 60-800F is a certified prime grade resin designed for production of extrusion coating used in general food packaging. HD 60-800F features a combination of excellent MVTR, good processability, grease resistance, low gel levels and improved stiffness and scuff resistance. HD 60-800F complies with FDA regulation 21CFR 177.1520 and with most international regulations concerning the use of Polyethylene in contact with food articles.

General Information			
Features	Low speed solidification crystal point Rigid, good High density Workability, good Good wear resistance Grease resistance Compliance of Food Exposure		
Uses	Food packaging		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Particle		
Processing Method	Extrusion coating		
Physical	Nominal Value	Unit	Test Method
Density	0.962	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	ASTM D1238

Additional Information			
------------------------	--	--	--

Test Made on injection molded Type 1 tension test specimen according to ASTM D2146

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT