Shanghai Potomer SG2

Flexible Polyvinyl Chloride

Shanghai Potomer International Trade Co., Ltd.

Message:

PVC suspension Resin is Calcium Carbide base, mainly used as sheet, pipe, window profiles and other molded parts. APPLICATIONS: cable sheathing and insulation, flexible films and sheets, water proof membranes, Flexible profiles

General Information		
Features	Good Flexibility	
Uses	Cable Jacketing	
	Film	
	Insulation	
	Membranes	
	Profiles	
	Sheet	
Processing Method	Calendering	
	Extrusion	
	Extrusion Blow Molding	
Physical	Nominal Value	Unit
Apparent Density	> 0.45	g/cm³
K (wear) Factor	73.0 to 74.0	
Sieve Analysis		
0.063mm sieve	> 90	%
0.25mm sieve	< 2.0	%
Viscosity	136 to 143	cm³/g
Volatile Matter	< 0.30	%
Conductivity	< 0.00500	S/m
Fish Eye	< 20.0	pcs/400 cm ²
Impurities	< 16.0	pcs
Whiteness - after 10min (160°C)	> 74	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

