Evermore PUR SA-2130M

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SA-2130M is a Polyurethane product. It is available in Asia Pacific. Applications of Evermore PUR SA-2130M include coating applications and fabrics/fibers. Primary characteristic: good adhesion.

General Information					
Features	Bondability				
Uses	Coating Applications				
	Textile Applications				
Elastomers	Nominal Value	Unit	Test Method		
Tensile Stress (100% Strain)	0.981 to 1.96	MPa	ASTM D412		

Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	0.981 to 1.96	MPa	ASTM D412
Tensile Strength (Yield)	14.7 to 24.5	MPa	ASTM D412
Tensile Elongation (Break)	200 to 400	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	60.0 to 80.0	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	29 to 32	%	
Solvents	DMF, TOL		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

