## **SUMILITE® CEL-4541**

Linear Low Density Polyethylene Sumitomo Bakelite Co., Ltd.

## Message:

SUMILITE® CEL-4541 is a linear low density polyethylene product. It can be processed by co-extrusion or thermoforming and is available in North America. SUMILITE® CEL-4541 application areas include packaging and movies.

Features include:

Good flexibility

Heat resistance

General Information			
Features	Good flexibility		
	Heat resistance, high		
	Soft		
Uses	Multilayer film		
	Food packaging		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Co-extrusion molding		
	Thermoforming		
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD: Yield, 120 µm	49.0	MPa	ASTM D882
TD: Yield, 120 µm	44.0	MPa	ASTM D882
Tensile Elongation			ASTM D882
MD: Fracture, 120 μm	410	%	ASTM D882
TD: Fracture, 120 µm	410	%	ASTM D882
Elastomers	Nominal Value	Unit	Test Method
Tear Strength			ASTM D624
Transverse flow	127	kN/m	ASTM D624
Flow	157	kN/m	ASTM D624
Optical	Nominal Value	Unit	Test Method
Transmittance (120 μm)	90.0	%	ASTM D1003
Additional Information			

In conformity with Notification No.370 of the MHLW Food Hygiene and Sanitation Law. The values listed as ASTM D882 were tested in accordance with JIS Z1702The values listed as ASTM D624 was tested in accordance with JIS K7128 CThe values listed as ASTM D1003 were tested in accordance with JIS Z7105Oxygen Gas Permeability, JIS K7126 B (OXTRAN), 25°C, 65% RH: 2 cm³/m²/24h/atm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

## Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



Page 2