

Evermore PUR SA-230P

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SA-230P is a Polyurethane product. It is available in Asia Pacific. Applications of Evermore PUR SA-230P include coating applications and fabrics/fibers. Primary characteristic: good adhesion.

General Information			
Features	Bondability		
Uses	Coating Applications		
	Textile Applications		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	1.96 to 3.92	MPa	ASTM D412
Tensile Strength (Yield)	14.7 to 24.5	MPa	ASTM D412
Tensile Elongation (Break)	200 to 400	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	80.0 to 120	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	43 to 47	%	
Solvents	DMF, MEK, TOL		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

