COSMOPLENE® AZ564

Polypropylene Copolymer

TPC, The Polyolefin Company (Singapore) Pte Ltd

Message:

COSMOPLENE AZ564 is high impact PP copolymer manufactured by gas phase process licensed from Sumitomo Chemical Co. Japan.

COSMOPLENE AZ564 is high flow, high stiffness, high impact copolymer grade which can perform faster injection cycle and thinner gauge.

COSMOPLENE AZ564 is specially designed for large item, wide area, thin gauge, low stress products such as tub and lid of washing machine, thin wall containers, TV back cover, automotive door trims etc.

General Information					
Features	High Flow				
	High Impact Resistance				
	High Stiffness				
	Impact Copolymer				
Uses	Appliance Components				
	Automotive Applications				
	Thin-walled Containers				
Agency Ratings	FDA 21 CFR 177.1520(c) 3.1a				
UL File Number	E108370				
Forms	Pellets				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	0.900	g/cm³	ASTM D792		
Melt Mass-Flow Rate (MFR)	30	g/10 min	ASTM D1238		
Molding Shrinkage			Internal Method		
Flow : 2.00 mm	1.5	%			
Across Flow : 2.00 mm	1.5	%			
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	90		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength			ASTM D638		
Yield	26.5	MPa			
Break	19.0	MPa			
Tensile Elongation (Break)	150	%	ASTM D638		
Flexural Modulus	1180	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C	40	J/m			
23°C	71	J/m			

Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (0.45					
MPa, Unannealed)	121	°C	ASTM D648		
Flammability	Nominal Value		Test Method		
Flame Rating	НВ		UL 94		
Injection	Nominal Value	Unit			
Rear Temperature	190 to 230	°C			
Middle Temperature	190 to 230	°C			
Front Temperature	190 to 230	°C			
Mold Temperature	30.0	°C			
Injection Pressure	6.86	MPa			
Clamp Tonnage	0.98	kN/cm²			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

