

OPTICITE™ SQZ Clear

Label Film

The Dow Chemical Company

Message:

OPTICITE™ SQZ Clear Polyolefin Label Film is a matte, clear label film for pressure-sensitive applications that require squeezability. Available in 3.0 mil thickness.

General Information			
Appearance	Clear/Transparent		
Forms	Film		
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	76	µm	ASTM D374
Film Thickness - Recommended / Available	3.0 mil (75 µ)		
Secant Modulus			ASTM D882
1% Secant, MD : 76 µm	524	MPa	
1% Secant, TD : 76 µm	538	MPa	
Tensile Strength			ASTM D882
MD : Break, 76 µm	24.1	MPa	
TD : Break, 76 µm	17.2	MPa	
Tensile Elongation			ASTM D882
MD : Break, 76 µm	260	%	
TD : Break, 76 µm	5.0	%	
Treatment ¹	55	dyne/cm	ASTM D2578
Yield (76.2 µm)	13.8	m ² /kg	ASTM D2103
Optical	Nominal Value		Test Method
Gloss			ASTM D2457
60°, 76.2 µm ²	47		
60°, 76.2 µm ³	62		
NOTE			
1.	Treatment on outside surface only.		
2.	TD		
3.	MD		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

