SumiDurez PM 937

Phenolic

SumiDurez Singapore Pte Ltd

Message:

PM 937 Phenolic is a single stage glass fiber, mineral/flour filled special purpose molding compound. It is especially designed for applications requiring high dimensional stability with excellent electric insulation property and good heat/flame resistance. Typical applications include coil bobbins, switches and terminal boards.

JIS Type EG-R

Filler / Reinforcement Features	Glass Fabric			
Features	Elastrias III. Institution			
	Electrically Insulating			
	Good Dimensional Stability			
	High Heat Resistance			
Uses	Bobbins			
	Connectors			
	Electrical Parts			
	Electrical/Electronic Applications			
	Switches			
Appearance	Black			
Forms	Granules			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.68	g/cm³	JIS K6911	
Apparent Density	0.74	g/cm³	JIS K6911	
Molding Shrinkage - Flow (Transfer				
Molded)	0.68	%	JIS K6911	
Water Absorption (24 hr)	0.25	%	JIS K6911	
Mechanical	Nominal Value	Unit	Test Method	
Flexural Strength	103	MPa	JIS K6911	
Compressive Strength	225	MPa	JIS K6911	
Impact	Nominal Value	Unit	Test Method	
Charpy Notched Impact Strength	3.0	kJ/m²	JIS K6911	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (1.8 MPa, Unannealed)	190	°C	JIS K6911	
Electrical	Nominal Value	Unit	Test Method	
Dielectric Strength ¹	11	kV/mm	JIS K6911	
Insulation Resistance			JIS K6911	
²	1.0E+12	ohms		

³	1.0E+11	ohms	
Flammability	Nominal Value	Unit	Test Method
Flame Rating (0.480 mm)	V-0		UL 94
NOTE			
1.	60 V/sec		
2.	Before Boiling		
3.	After Boiling		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

