

# EPAMOULD 685A26

Thermoplastic Polyurethane Elastomer (Polyester)

Epaflex Polyurethanes S.R.L.

## Message:

The EPAMOULD 600 series was created to meet the most stringent performance requirements in the footwear industry. Over time it has evolved to include the existing range of products, all made from polyester, which comprises:  
a series of products plasticized, phthalate-free and high fluidity  
a number of products to be free from plasticizers, robust and suitable to the technical sector.

General Information		
Additive	Beeswax	
	Plasticizer	
Features	Plasticized	
	High liquidity	
Uses	Footwear	
Appearance	Clear/transparent	
Processing Method	Injection molding	
Physical	Nominal Value	Unit
Density	1.18	g/cm <sup>3</sup>
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	85	
Mechanical	Nominal Value	Unit
Abrasion Loss	45.0	mm <sup>3</sup>

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

