

# DPE® 6611

Low Density Polyethylene

DuPont Packaging & Industrial Polymers

## Message:

DPE® 6611 is a Low Density Polyethylene material. It is available in North America for compounding or extrusion.

Typical application of DPE® 6611: Additive/Masterbatch

General Information	
Uses	Compounding
Forms	Pellets
Processing Method	Compounding
	Extrusion

Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	232	°C
Cylinder Zone 2 Temp.	288	°C
Cylinder Zone 3 Temp.	304	°C
Cylinder Zone 4 Temp.	310	°C
Cylinder Zone 5 Temp.	310	°C
Adapter Temperature	310	°C
Die Temperature	310	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

