

Aegis® MBM

Polyamide 6

Honeywell

Message:

Aegis® MBM is a terminated, non-delustered, bright medium dye, medium viscosity nylon 6 resin for carpet fiber and synthetic turf extrusion applications.

General Information			
Features	Medium viscosity		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.13	g/cm ³	ASTM D1505
Moisture Content		%	ASTM D6869
Relative viscosity-@ 96% SAV	2.83		
Viscosity-FAV	58.0 - 64.0		ASTM D789
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	220	°C	ASTM D3418
Additional Information			
Extractable Content: <1.1% using test method SOP-702-307			
Extrusion	Nominal Value	Unit	
Drying Temperature	80.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT