

Huaxia Shenzhou DS606

Fluoropolymer

Shandong Huaxia Shenzhou New Material Co., Ltd.

Message:

Fluorinated ethylene-propylene powder, as a copolymer of tetrafluoroethylene and hexafluoropropylene, has good heat stability, outstanding chemical inertness, excellent electrical insulation and low friction coefficient, and can be processed by a thermoplastic processing method. It can mix with telfon powder.
Execution standard: Q/DYS 003-2007

| General Information | | |
|---------------------------|--------------------------|----------|
| Features | Copolymer | |
| | Electrically Insulating | |
| | Good Chemical Resistance | |
| | Good Thermal Stability | |
| | Low Friction | |
| Uses | Liners | |
| Appearance | White | |
| Forms | Powder | |
| Physical | Nominal Value | Unit |
| Melt Mass-Flow Rate (MFR) | 0.80 to 2.0 | g/10 min |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT