

Polylite® ProCast PLUS 32144-38

Thermoset Polyester

Reichhold Chemicals, Inc.

Message:

Polylite® ProCast PLUS 32144-38 is a thermosetting polyester product. It can be processed by casting and is available in North America.

Features include:

Rapid Prototyping Cycle

Good toughness

Impact resistance

Heat resistance

Medium viscosity

General Information			
Features	Impact resistance, high Fast molding cycle Fast curing Good cracking resistance Good thermal shock resistance Good toughness Elastic Medium viscosity		
Forms	Liquid		
Processing Method	Casting		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.14	g/cm ³	ASTM D792
Thermoset	Nominal Value	Unit	Test Method
Pot Life (25°C)	6.0 - 8.0	min	
Shelf Life (25°C)	13	wk	
Thermoset Mix Viscosity (25°C)	1050	cP	ASTM D2393
Additional Information			

Specific Gravity, Test Method Unspecified, 25°C: 1.10 to 1.18

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT