

Magnobond 75

Epoxy; Epoxide
Magnolia Plastics, Inc.

Message:
Magnobond 75 is an Epoxy; Epoxide (Epoxy) product. It is available in North America. Typical application: Foam. Primary characteristic: flame retardant.

General Information			
Additive	Flame Retardant		
Features	Flame Retardant		
Uses	Foam		
Forms	Paste		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.718	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Compressive Strength	31.0	MPa	ASTM D695
Shear Strength	11.0	MPa	ASTM D732
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Weight: 17		
Resin	Mix Ratio by Weight: 100		
Pot Life	30	min	
Demold Time (25°C)	720	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT