

APEX® 04-A769R-90NT

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX® 04-A769R-90NT is a Flexible Polyvinyl Chloride material. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America for extrusion.

Important attributes of APEX® 04-A769R-90NT are:

Plasticized

Sterilizable

General Information			
Additive	Plasticizer		
Features	Non-Phthalate Plasticizer		
	Radiation Sterilizable		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.25	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	90		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	20.6	MPa	ASTM D638
Tensile Elongation (Break)	310	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	50.0	°C	ASTM D794
Brittleness Temperature	-51.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT