

APEX® 90-A472R-55-NT

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX® 90-A472R-55-NT is a Flexible Polyvinyl Chloride material. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America for injection molding.

Important attributes of APEX® 90-A472R-55-NT are:

- Plasticized
- Radiation (Gamma) Resistant
- Sterilizable

Typical applications include:

- Caps/Lids/Closures
- Engineering/Industrial Parts
- Medical/Healthcare

General Information			
Additive	Plasticizer		
Features	DEHP Plasticizer		
	Radiation (Gamma) Resistant		
	Radiation Sterilizable		
Uses	Caps		
	Medical/Healthcare Applications		
	Valves/Valve Parts		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.15	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	55		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	9.65	MPa	ASTM D638
Tensile Elongation (Break)	370	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

