Pujie CPE230A

Chlorinated Polyethylene

Zhanhua Pujie Chemical Technology Co.,Ltd

Message:

CM30,High molecular weight, superior mechanical performance, high modules, low chlorine content, excellent low temperature property, excellent absorption ability to filler.

| General Information | | |
|----------------------------------|---------------------------------|-------|
| Features | Rigidity, high | |
| | High molecular weight | |
| | Low temperature resistance | |
| | | |
| Uses | Industrial application | |
| | Pipe | |
| | Application in Automobile Field | |
| | | |
| Physical | Nominal Value | Unit |
| Apparent Density | > 0.50 | g/cm³ |
| Mooney Viscosity (ML 1+4, 125°C) | 80 - 85 | MU |
| Chlorine Content | 29.0 - 31.0 | wt% |
| Hardness | Nominal Value | Unit |
| Durometer Hardness (Shore A) | < 60 | |
| Mechanical | Nominal Value | Unit |
| Tensile Strength | > 8.00 | MPa |
| Tensile Elongation (Break) | > 750 | % |
| Thermal | Nominal Value | Unit |
| Heat of Fusion | | J/g |
| | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

pcs/50 g

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Impurities

Volatiles

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

