

DOW™ LLDPE 1630.11T

Linear Low Density Polyethylene Resin

The Dow Chemical Company

Message:

LLDPE 1613.11T is a Linear Low Density Polyethylene Resin, 1-Hexene, 1-Octene terpolymer, produced in the Solution process. This resin is designed to be used in cast extrusion to produce films for industrial applications and consumer packaging.

Complies with:

Europe Commission Regulation (EU) No 10/2011 (See NOTES)

U.S. FDA 21 CFR 177.1520(c) 3.2a

Consult the regulations for complete details.

General Information			
Additive	Antiblock (2500 ppm)		
	Slip (1000 ppm)		
Agency Ratings	EU No 10/2011		
	FDA 21 CFR 177.1520(c) 3.2a		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.922	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.1	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT