

MOSTEN MA 760

Polypropylene Impact Copolymer

UNIPETROL RPA

Message:

Polypropylene Mosten MA 760 is a high melt flow block copolymer with antistatic additivation, intended for injection moulding of parts requiring high flowability and impact strength. It is suitable for thin walled injection moulding into multiple moulds. Typical application is production of various foodstuffs packaging, boxes, technical parts, crates (clap-boxes), etc.

Mosten MA 760 meets the hygienic regulations concerning contact with food of European Union (Commission Directives), Germany (BfR) and USA (FDA). The product is not classified as hazardous preparation according to Directive 1999/45/EC

General Information			
Additive	Antistatic		
Features	Antistatic		
	Block Copolymer		
	Food Contact Acceptable		
	High Flow		
	High Impact Resistance		
Uses	Containers		
	Crates		
	Engineering Parts		
	Food Packaging		
Agency Ratings	BfR Food Contact, Unspecified Rating		
	EU 1999/45/EC		
	EU Food Contact, Unspecified Rating		
	FDA Food Contact, Unspecified Rating		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	60	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	25.0	MPa	ISO 527-2
Tensile Strain (Break)	35	%	ISO 527-2
Flexural Modulus	1350	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength			ISO 179
-20°C	4.0	kJ/m²	
23°C	8.0	kJ/m²	
Thermal	Nominal Value	Unit	Test Method


Heat Deflection Temperature (1.8 MPa, Unannealed)	56.0	°C	ISO 75-2/A
Vicat Softening Temperature	151	°C	ISO 306

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
 Phone: +86 13424755533
 Email: sales@su-jiao.com
 No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT