Bluestar Epoxy WSR6101

Epoxy; Epoxide

Bluestar New Chemical Materials Co. Ltd

Message:

Bisphenol-A liquid epoxy resin

Applications: This product is general epoxy resin. It has fine electricity insulating property, good cohesiveness and good property for process operation. It is used widely to prepare non-solvent or less-solvent coatings, glass fiber reinforced plastics, composite, adhesive, casting, etc.

General Information			
Features	Electrically Insulating		
	Good Processability		
	High Viscosity		
Uses	Adhesives		
	Coating Applications		
Appearance	Transparent - Slight Yello	w	
Forms	Liquid		
Processing Method	Casting		
Thermal	Nominal Value	Unit	
Softening Point	12 to 32	°C	
Epoxy Equivalent	213 to 270	g/eq	
Volatiles	< 1.0	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

