

# Pearlthane® MB-9010

Thermoplastic Polyurethane Elastomer

Lubrizol Advanced Materials, Inc.

## Message:

PEARLTHANE® MB-9010 is a TPU-based colour masterbatch, supplied in the form of homogeneously white-coloured pellets. It is specially intended for colouring TPUs (either polyester or polyether-based), for extrusion, injection moulding or calendering processes.

PEARLTHANE® MB-9010 can be mixed with any items of our PEARLTHANE® or PEARLCOAT® lines (either polyester or polyether-based) intended for applications obtained by extrusion, injection moulding or calendering.

A 2 % usage level (on TPU, by weight) is recommended. Higher levels can be considered, depending on the requirements of the end-product.

General Information	
Uses	Masterbatch
Agency Ratings	EC 1907/2006 (REACH)
Appearance	White
Forms	Pellets
Processing Method	Calendering Extrusion Injection Molding

Physical	Nominal Value	Unit	Test Method
Apparent Density	1.05	g/cm <sup>3</sup>	ASTM D1895
Light Fastness - (1-8) scale of blue tones	8		DIN 53389
Color Number	RAL 9010		
Titanium Dioxide	60	%	
Injection	Nominal Value	Unit	
Drying Temperature	100 to 110	°C	
Drying Time	1.0 to 2.0	hr	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT