

APEX® 65002

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX®65002 is a flexible polyvinyl chloride material. This product is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. The processing method is: extrusion.

APEX®The main features of the 65002 are:

ROHS certification

Flame Retardant

Typical application areas include:

Wire and cable

Electrical/electronic applications

General Information			
Features	Flame retardancy		
Uses	Communication wire sheath		
Wire Types	CL2		
	CL3		
	CM		
	FPL		
	MP		
	OFN		
Agency Ratings	NEC Article 725		
	NEC Article 760		
	NEC Article 770		
	NEC Article 800		
	UL 13		
	UL 1424		
RoHS Compliance	UL 444		
	RoHS compliance		
	Opacity		
Appearance	Particle		
Forms	Extrusion		
Processing Method			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.31	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C, 10 sec)	73		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	22.1	MPa	ASTM D638
Tensile Elongation (Break)	340	%	ASTM D638

Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-28.0	°C	ASTM D746
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	30	%	ASTM D2863

Additional Information

无铅原为95-A0542E-99温度额定值:105 °C耐日光性UL认证:否

Extrusion	Nominal Value	Unit
Melt Temperature	191	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

